

屋内用
片扉 IP2XD
両扉 IP2XC

ライトベージュ塗装
LB色(5Y7 1)
白塗工G26-70B

クリーム塗装
クリーム色(2.5Y9 1)
日塗工G22-90B

フカサ 160mm

単位/mm

納期区分		木製基板付		納期区分		鉄製基板付		標準価格 円	扉形式	外形寸法			取付基板寸法		有効フカサ*		製品質量 kg	
LB色	C色	品名記号	LB色	C色	品名記号	ヨコ	タテ			フカサ	ヨコ	タテ	Bタイプ	Sタイプ	Bタイプ	Sタイプ		
◎	◎	B16-812-1	◎	◎	S16-812-1			63,000	片扉	800	1,200	160	720	1,120	128	141	45.9	53.1
◎	◎	B16-812-2	◎	◎	S16-812-2			66,500	両扉	〃	〃	〃	〃	〃	〃	〃	47.8	54.9
◎	◎	B16-814-1	◎	◎	S16-814-1			70,000	片扉	〃	1,400	〃	〃	1,320	〃	〃	57.6	66.0
◎	◎	B16-814-2	③	③	S16-814-2			73,500	両扉	〃	〃	〃	〃	〃	〃	〃	59.7	68.1
◎	◎	B16-816-1	◎	◎	S16-816-1			82,000	片扉	〃	1,600	〃	〃	1,520	〃	〃	65.0	74.6
◎	◎	B16-816-2	③	③	S16-816-2			85,500	両扉	〃	〃	〃	〃	〃	〃	〃	67.2	76.8
◎	◎	B16-94-2	③	③	S16-94-2			40,500	両扉	900	400	160	820	320	128	141	21.9	24.4
◎	◎	B16-95-2	◎	◎	S16-95-2			42,500	〃	〃	500	〃	〃	420	〃	〃	25.7	28.9
◎	◎	B16-104-2	③	③	S16-104-2			50,500	両扉	1,000	400	160	920	320	128	135	23.9	26.7
◎	◎	B16-105-2	◎	◎	S16-105-2			52,000	〃	〃	500	〃	〃	420	〃	〃	28.0	31.6
◎	◎	B16-106-2	◎	◎	S16-106-2			54,000	〃	〃	600	〃	〃	520	〃	〃	32.2	36.5
◎	◎	B16-107-2	◎	◎	S16-107-2			56,000	〃	〃	700	〃	〃	620	〃	〃	36.3	41.4
◎	◎	B16-108-2	◎	◎	S16-108-2			58,500	〃	〃	800	〃	〃	720	〃	〃	40.4	46.3
◎	◎	B16-109-2	◎	◎	S16-109-2			66,500	〃	〃	900	〃	〃	820	〃	〃	44.6	51.3
◎	◎	B16-1010-2	◎	◎	S16-1010-2			68,500	〃	〃	1,000	〃	〃	920	〃	〃	49.1	57.1
◎	◎	B16-1011-2	◎	◎	S16-1011-2			70,000	〃	〃	1,100	〃	〃	1,020	〃	〃	53.2	62.1
◎	◎	B16-1012-2	◎	◎	S16-1012-2			72,000	〃	〃	1,200	〃	〃	1,120	〃	〃	57.4	67.0
◎	◎	B16-1014-2	◎	◎	S16-1014-2			85,500	〃	〃	1,400	〃	〃	1,320	〃	〃	71.0	82.3
◎	◎	B16-1016-2	◎	◎	S16-1016-2			104,000	〃	〃	1,600	〃	〃	1,520	〃	〃	79.9	92.8
◎	◎	B16-119-2	◎	◎	S16-119-2			68,500	両扉	1,100	900	160	1,020	820	128	135	48.3	55.7
③	③	B16-124-2	③	③	S16-124-2			50,500	両扉	1,200	400	160	1,120	320	128	135	27.9	31.2
◎	◎	B16-125-2	③	③	S16-125-2			54,000	〃	〃	500	〃	〃	420	〃	〃	32.7	37.0
◎	◎	B16-1610-2	◎	◎	S16-1610-2			104,000	両扉	1,600	1,000	160	1,520	920	128	135	78.8	91.7

フカサ 180mm

代	代	B18-355	◎	◎	S18-355			21,500	片扉	350	500	180	270	420	148	161	12.0	13.1
◎	◎	B18-46	◎	◎	S18-46			27,500	片扉	400	600	180	320	520	148	161	15.2	16.8
◎	◎	B18-57	◎	◎	S18-57			34,000	片扉	500	700	180	420	620	148	161	20.4	22.8
◎	◎	B18-69	◎	◎	S18-69			43,500	片扉	600	900	180	520	820	148	161	28.9	32.8
◎	◎	B18-611	◎	◎	S18-611			52,500	〃	〃	1,100	〃	〃	1,020	〃	155	34.5	39.3

フカサ 200mm

◎	◎	B20-33	◎	◎	S20-33			14,500	片扉	300	300	200	220	220	168	181	7.7	8.3
◎	◎	B20-34	◎	◎	S20-34			19,500	〃	〃	400	〃	〃	320	〃	〃	9.5	10.2
◎	◎	B20-35	◎	◎	S20-35			21,500	〃	〃	500	〃	〃	420	〃	〃	11.2	12.1
◎	◎	B20-36	◎	◎	S20-36			25,500	〃	〃	600	〃	〃	520	〃	〃	13.0	14.1
◎	◎	B20-43	◎	◎	S20-43			19,500	片扉	400	300	200	320	220	168	181	9.5	10.2
◎	◎	B20-44	◎	◎	S20-44			22,500	〃	〃	400	〃	〃	320	〃	〃	11.6	12.6
◎	◎	B20-45	◎	◎	S20-45			25,500	〃	〃	500	〃	〃	420	〃	〃	13.7	15.0
◎	◎	B20-46	◎	◎	S20-46			27,500	〃	〃	600	〃	〃	520	〃	〃	15.8	17.3
◎	◎	B20-47	◎	◎	S20-47			33,000	〃	〃	700	〃	〃	620	〃	〃	17.8	19.7
◎	◎	B20-48	◎	◎	S20-48			36,000	〃	〃	800	〃	〃	720	〃	〃	19.9	22.1
◎	◎	B20-410	◎	◎	S20-410			42,500	〃	〃	1,000	〃	〃	920	〃	175	24.2	27.0
◎	◎	B20-412	◎	◎	S20-412			46,500	〃	〃	1,200	〃	〃	1,120	〃	〃	28.4	31.7
◎	◎	B20-457	◎	◎	S20-457			35,000	片扉	450	700	200	370	620	168	181	19.4	21.6
◎	◎	B20-53	◎	◎	S20-53			21,500	片扉	500	300	200	420	220	168	181	11.3	12.2
◎	◎	B20-54	◎	◎	S20-54			25,500	〃	〃	400	〃	〃	320	〃	〃	13.7	15.0
◎	◎	B20-55	◎	◎	S20-55			27,500	〃	〃	500	〃	〃	420	〃	〃	16.1	17.8
◎	◎	B20-56	◎	◎	S20-56			31,000	〃	〃	600	〃	〃	520	〃	〃	18.6	20.6
◎	◎	B20-57	◎	◎	S20-57			35,000	〃	〃	700	〃	〃	620	〃	〃	21.0	23.4
◎	◎	B20-58	◎	◎	S20-58			39,000	〃	〃	800	〃	〃	720	〃	〃	23.4	26.2
◎	◎	B20-59	◎	◎	S20-59			42,000	〃	〃	900	〃	〃	820	〃	〃	25.8	29.0

◎代理店様在庫品 ◎物流センター在庫品 ①③⑤⑦標準品(納期別) (受)受注品 ●有効フカサはハンドル部・フレーム等により減少しますのでご注意ください。
★両扉の合せ部の有効フカサは23mm引いた寸法となります。

※印は標準品です。 ※印は標準品です。

キャビネット

盤用

防塵・防水形

小型F/A用

自立形

熱対策用

情報通信用

特定用途別

計器器用

スリムレス

キャビネット

技術資料