

絶縁被覆付圧着端子

INSULATED TERMINALS

RoHS (黄色以外)

RoHS (黄色)

単位:mm

呼 び	標準色	φd2	B	L	F	φD	φ	t	電線抱合容量(参考)			適合工具	一箱入数
									単線mm	燃線mm ²	AWG		
2	青	3.3	8.5	21.0	7.25	4.0	9.5	0.8	1.14	1.04	16-14	4D 34 AC-5ND (4号ヘッド)	1,000 (100×10)
			6.4	16.9	4.2								
			6.6	20.1	7.3								
			5.8	19.7									
		3.8	6.4	16.9	4.2								
			6.6	20.1	7.3								
		4.4	8.5	21.0	7.25								
			6.6	18.1	5.3								
				20.1	7.3								
		5.4	9.5	21.7	7.45								
			8.5	21	7.25								
		6.6	12	26.3	10.8								
		8.6											
		10.7	13.6	30	13.7								
		13.2	19	35.5	16.5								
		15.2	27	44	21								
		17.2											
		19.2											
		21.2											
		5.5	黄	3.3	9.5								27.4
8.0	26.3				8.0								
7.0	25.8				8.0								
9.5	27.4			8.35									
3.8	8.0			26.3	8.0								
	7.0			25.8									
4.4	9.5			27.4	8.35								
	8.0			26.3	8.0								
				7.0		25.8							
5.4	9.5			27.4	8.35								
	8.0			26.3	8.0								
6.6	12			33.1	12.8								
	13.3			30.8	9.85								
				9.5	27.4	8.35							
8.6	15			36	14.2								
	13.3			30.8	9.85								
				12	33.1	12.8							
10.7	15			36	14.2								
13.2	19.2			40.3	16.4								
15.2	32			55.8	25.5								
17.2													
19.2													
21.2													
100													

- (注意) ・各部の寸法は予告なく変更することがあります。
 ・UL, CSA登録品としてご使用の場合、ご注文時にご指示して下さい。
 ・UL, CSA登録工具は、パッケージの説明書をご覧ください。
 ・絶縁体の色は、赤、青、黄、透明、白、黒、緑があります。
 ・()内はJIS型番です。
 ・UL, CSA登録品は記号がRAVになります。
 ・絶縁体の材質は塩化ビニル(最高使用温度75℃)です。