



裸圧着端子 (R形)



丸形端子

呼び	在庫	各 部 の 寸 法								適合電線範囲			適合工具	一箱入数	
		d ₂	B	L	F	E	D	d ₁	T	単線mm	撚線mm ²	AWG			
0.3-2		2.2													
0.3-3		3.2	5.2	12.5	5.9										
0.3-3.5		3.7				4.0	2.3	0.8	0.65	0.32	0.1	26-24	DS031	1,000	
0.3-4		4.3	6.6	15.0	7.7					0.6	0.3		DH-1B		
													AC-5N-D		
0.5-2		2.2													
0.5-3		3.2	5.2	12.5	5.9										
0.5-3.5		3.7				4.0	2.3	1.2	0.5	0.5	0.2	24-20	DS031	1,000	
0.5-4		4.3	6.6	15.0	7.7					0.8	0.5		DH-1B		
0.5-5		5.3	8.0		7.0								AC-5N-D		
1.25-2		2.5													
1.25-3			5.5	12.0	4.8										
1.25-M3				13.8											
1.25-V3		3.2	6.6	14.4	6.6										
1.25-L3			8.0	15.5	7.5										
1.25-S3.5				12.0	4.8										
1.25-M3.5		3.7	5.5	13.8						0.57	0.25	22-16	DS031	1,000	
1.25-3.5						4.5	3.4	1.7	0.8	0.6	0.3		ミ12		
1.25-S4			6.6	14.4	6.6					1.44	1.65		5N18		
1.25-4		4.3											DH-1B		
1.25-5			8.0	15.5	7.5								AC-5N-D		
1.25-L5		5.3		18.5											
1.25-6		6.4	11.5	20.2	10.0										
1.25-8		8.4													
1.25-10		10.5	13.6	21.8	10.5										500
1.25-12		13.0	22.0	29.5	14.0										400
2-3			6.6	13.0	5.2										
2-M3		3.2		12.4											
2-L3			5.5	13.7											
2-M3.5			5.8	13.9	6.5										
2-3.5		3.7		13.0	5.2										
2-L3.5				16.0	8.3										
2-M4			6.6	14.3	6.5										
2-S4		4.3		16.0	8.3										
2-4			8.5	16.5						1.14	1.04	16-14	ミ12		
2-S5					7.8					0.6	0.3		5N18		
2-5		5.3	9.5	17.0		4.5	4.2	2.3	0.8	1.82	2.63		214A		
2-6		6.4	12.0	21.5	11.0								DH-1B		
2-8													AC-5N-D		
2-A8		8.4	18.0	27.5	14.0								REC-14A		
2-B8			16.0	28.5	16.0										500
2-10			14.5	24.0	12.3										
2-A10		10.5	18.0	27.5	14.0										400
2-B10			20.0	32.5	18.0										400
2-12			17.0	26.9	13.9										500
2-A12		13.0	22.0	29.5	14.0										400
3.5-S4		4.3	7.0	17.1											
3.5-4					8.3										
3.5-5		5.3	8.5	17.8						1.82	2.63		5N18		
3.5-6		6.4	12.0	21.8	10.5	5.3	5.0	3.0	1.0	2.4	4.6	12	214A		
3.5-8		8.4											DH-1B		
3.5-10		10.5	14.5	25.0	12.5								AC-5N-D		
3.5-12		13.0	20.0	31.0	15.7								REC-14A		

- 各呼びの 印は、JIS規格品、UL登録品、CSA登録品です。
- UL登録品又はCSA登録品としてご使用の際は、注文時にご指示ください。カートンがUL品用又はCSA品用となります。
- 上記寸法表にかぎらず特注品もご相談ください。