



形番	規格	寸法(mm)							標準色	適用電線範囲 撚線(mm ²)	適用圧着工具			1箱 入数 (個)	
		φd2	B	L	F	ℓ	φD	板厚			手動	空気圧式	油圧式		
FV5.5-S3.3	Ⓛ Ⓢ	3.2	7.2	23.0	5.9	13.5	6.8	1.0	黄	2.63~6.64 {3.5(AWG#12)} {5.5(AWG#10)}	YNT-1210S	YA-4 YAT-4A YAD-4A	BCT-0514	500	
FV5.5-3	Ⓛ Ⓢ		9.5	26.5	8.3										
FV5.5-S3	Ⓛ Ⓢ	3.7	7.2	23.0	5.9										
FV5.5-S4	Ⓛ Ⓢ		9.5	26.5	8.3										
FV5.5-4(RBA5.5-4)	Ⓛ Ⓢ Ⓜ	4.3	13.2	29.1	9.0										
FV5.5-5(RBA5.5-5)	Ⓛ Ⓢ Ⓜ		12.0	32.5	13.0										
FV5.5-S5	Ⓛ Ⓢ	5.3	13.2	29.1	9.0										
FV5.5-6(RBA5.5-6)	Ⓛ Ⓢ Ⓜ		12.0	32.5	13.0										
FV5.5-S6	Ⓛ Ⓢ	6.4	13.2	29.1	9.0										
FV5.5-S8	Ⓛ Ⓢ		15.0	34.7	13.7										
FV5.5-8(RBA5.5-8)	Ⓛ Ⓢ Ⓜ	8.4	15.0	34.7	13.7										
FV5.5-10(RBA5.5-10)	Ⓛ Ⓢ Ⓜ		13.0	19.2	39.1	16.0									
FV5.5-12	Ⓛ Ⓢ	10.5	13.0	19.2	39.1	16.0									
FV5.5-14	Ⓛ Ⓢ		15.0	19.2	39.1	16.0									
FV5.5-16	Ⓛ Ⓢ	13.0	32.0	54.8	25.3	13.5	6.8	1.0	黄	2.63~6.64 {3.5(AWG#12)} {5.5(AWG#10)}	YNT-1210S	YA-4 YAT-4A YAD-4A	BCT-0514	250	
FV5.5-18	Ⓛ Ⓢ														17.0
FV5.5-18	Ⓛ Ⓢ														19.0
FV5.5-20	Ⓛ Ⓢ														21.0

注1) ()はJIS規格形番を示します。なお、JIS規格形番製品とJST形番製品は同一品です。規格No.JIS C 2805
 注2) 本製品の中には多少納期を要するものもあります。